

NOTES:

- 1. LF. = LOAD FACTOR TO BE USED TO DETERMINE 3 EDGE BEARING BASED ON TYPE OF EMBEDMENT.
- 2. FREE-FALL OF CONCRETE NOT TO EXCEED 5 FT.
- 3. P = Rho FOR STEEL %
- 4. Bc = OUTSIDE DIAMETER OF PIPE
- 5. Bd = TRENCH WIDTH
- 6. GREEN TRACER TAPE SHALL BE PLACED OVER ALL SANITARY SEWER MAINS.
- 7. BLUE TRACER WIRE, AWG #12, SHALL BE PLACED OVER ALL WATER MAINS AND ROUTED THROUGH VÄLVE STACKS.
- 8. CLASS "A" AND "A-1" EMBEDMENT MAY BE USED WHEN APPROVED BY THE CITY ENGINEER FOR EMBEDMENT OF A WATER OR SANITARY SEWER PIPE WHICH PASSES BENEATH A STORM DRAIN PIPE.



 $\underline{\text{NOTE}}\colon$ STANDARDS ARE ADOPTED FROM THE NCTOG STANDARD DRAWINGS DATED NOV. '96, WITH LOCAL EXCEPTIONS.

2				
ö				
Ë				
ď	NO.	LOCAL EXCEPTION	BY	DATE



COMPACTED 3/4" CRUSHED LIMESTÔNE

STANDARD CONSTRUCTION DETAILS **EMBEDMENT CLASS "A" AND "A-1"**

STD. SPEC. REFERENCE 504, 702.

CITY OF COPPELL DALLAS COUNTY, TEXAS

CLASS "A-1" CLASS "B" CONCRETE CAP PLAIN CONC. LF 2.8 N.T.S.

CLASS "B" PLAIN

-SUITABLE NATIVE MATERIAL

1/2 Bc

1/4 Bc

3" MIN.

6" MIN. IN ROCK


COMPACTED TO 95% STANDARD PROCTOR DENSITY

OR REINFORCED

CONCRETE.

REINF. CONC. LF 3.4 P=0.4% REINF. CONC. LF 4.8 P=1.0%

STANDARD DETAIL 3010



STORM DRAIN EMBEDMENT

North Central Texas Council of Governmen


NOTE: STANDARDS ARE ADOPTED FROM THE NCTOG STANDARD DRAWINGS DATED NOV. '96, WITH LOCAL EXCEPTIONS.

ΞI				
륍				
鯵				
ö				
Ë				
٦	NO.	LOCAL EXCEPTION	BY	DATE



STANDARD CONSTRUCTION DETAILS
EMBEDMENT
STORM DRAIN
CITY OF COPPELL DALLAS COUNTY, TEXAS

STD. SPEC. REFERENCE 508. STANDARD DETAIL 3020



WATER MAIN EMBEDMENT

(UNLESS MODIFIED BY APPROVED CONSTRUCTION PLANS)
N.T.S.

NOTES:

- 1. BLUE TRACER WIRE, AWG #12, SHALL BE PLACED OVER ALL WATER MAINS AND ROUTED THROUGH VALVE STACKS.
- 2. WATER LINE MINIMUM COVER IS 42" TO TOP OF PIPE.

North Central Texas Council of Governments


NOTE: STANDARDS ARE ADOPTED FROM THE NCTOG STANDARD DRAWINGS DATED NOV. '96, WITH LOCAL EXCEPTIONS.

3			
NO.	LOCAL EXCEPTION	BY	DATE



STANDARD CONSTRUCTI	ON DETAILS
EMBEDMENT	
WATER MAIN	
CITY OF COPPELL DALLAS COU	INTY, TEXAS

STD. SPEC. REFERENCE 504., 506. STANDARD DETAIL 3030



SANITARY SEWER LINE EMBEDMENT

(UNLESS MODIFIED BY APPROVED CONSTRUCTION PLANS)
N.T.S.

NOTE:

1. GREEN TRACER TAPE SHALL BE PLACED OVER ALL SANITARY SEWER MAINS.

North Central Texas Council of Governmen

NOTE: STANDARDS ARE ADOPTED FROM THE NCTOG STANDARD DRAWINGS DATED NOV. '96, WITH LOCAL EXCEPTIONS.


ä				
Ë				
ì	NO.	LOCAL EXCEPTION	BY	DATE



STANDARD CONSTRUCTION DETAILS
EMBEDMENT
SANITARY SEWER

CITY OF COPPELL DALLAS COUNTY, TEXAS

STD. SPEC. REFERENCE 504., 507. STANDARD DETAIL 3050



NOTES:

- 1. D = INSIDE DIAMETER OF PIPE
- 2. Bd = TRENCH WIDTH
- 3. TRACER TAPE SHALL BE PLACED OVER ALL SANITARY SEWER MAINS.
- 4. BLUE TRACER WIRE, AWG #12, SHALL BE PLACED OVER ALL WATER MAINS.

North Central Texas Council of Governmen


NOTE: STANDARDS ARE ADOPTED FROM THE NCTOG STANDARD DRAWINGS DATED NOV. '96, WITH LOCAL EXCEPTIONS.

}[
'n				
<u> </u>				
[]*	NO.	LOCAL EXCEPTION	BY	DATE



STANDARD CONSTRUCTION DETAILS				
EMBEDMENT				
CLASS "G" AND "G-1"				
CITY OF COPPELL DALLAS COUNTY, TEXAS				

STD. SPEC. REFERENCE 504., 702. STANDARD DETAIL 3060



T H E - C | T Y - O F

JUL. '06

JUL. '06

DATE

SWL

BY

PAVEMENT CUTS

REMOVAL AND REPLACEMENT

CITY OF COPPELL DALLAS COUNTY, TEXAS

402., 504., 702.

STANDARD DETAIL


3070

NO.

MODIFY NOTES 1 AND 2.

ADD PAVEMENT REPAIR DETAIL.

LOCAL EXCEPTION



SWL

BY

JUL. '06

DATE

501., 503., 509.

STANDARD DETAIL

3090

ENCASEMENT

ROADWAY CROSSING BORE


CITY OF COPPELL DALLAS COUNTY, TEXAS

PATH: S:\Standard_Details\New_De

NO.

ADD 5' DIMENSION.

LOCAL EXCEPTION



- OF THE CONDUIT.
- 2. THE LOCATION OF THE INTERSECTION OF THE CONDUIT AND THE BACK OF PAVING SHALL BE MARKED WITH A CHISELED "X" AND RED PAINT.
- 3. A NYLON CORD SHALL BE PLACED IN ALL CONDUIT UNDER PAVEMENT. CORD SHALL EXTEND A MINIMUM OF 1' FROM THE CONDUIT END.
- 4. ALL PIPE JOINTS SHALL BE SOLVENT WELDED.
- 5. ALL CONDUIT/SLEEVING SHALL BE SCHEDULE 40.

NOTE: STANDARDS ARE ADOPTED FROM THE NCTOG STANDARD DRAWINGS DATED NOV. '96, WITH LOCAL EXCEPTIONS.

'n				
Ë				
1	NO.	LOCAL EXCEPTION	BY	DATE



STANDARD CONSTRUCTION DETAILS
GENERAL UNDERGROUND CONDUIT
IRRIGATION SLEEVING AND ELECTRICAL CONDUIT
CITY OF COPPELL DALLAS COUNTY, TEXAS

STD. SPEC. REFERENCE 805. STANDARD DETAIL 3095

1. CONDUIT SHALL NOT BE PLACED WHERE IT IS LIKELY TO BE DAMAGED.

North Central Texas Council of Governmen

NOTE: STANDARDS ARE ADOPTED FROM THE NCTOG STANDARD DRAWINGS DATED NOV. '96, WITH LOCAL EXCEPTIONS.

NO.	LOCAL EXCEPTION	BY	DATE



STANDARD CONSTRUCTION DETAILS

GENERAL UNDERGROUND CONDUIT

GENERAL NOTES AND TESTING

STD. SPEC. REFERENCE

CITY OF COPPELL DALLAS COUNTY, TEXAS

STANDARD DETAIL 3100